

PRODUCT DESCRIPTION

Xtreme 8005 C3 ECO GAS 5W40 is a synthetic lubricant of last generation made with carefully selected raw materials and formulated to guarantee exceptional performance in modern dual-fuel engines that include CNG or LPG in pairs with gasoline or diesel engines.

Xtreme 8005 C3 ECO GAS 5W40 provides the following properties:

- High wear protection extending the life of the engine,
- Excellent resistance to oxidation and high thermal stability,
- Excellent low temperature property that guarantees total protection to the engine from the start,
- High stability at high temperature, which ensures low viscosity loss in extreme service conditions.

APPLICATIONS

Xtreme 8005 C3 ECO GAS 5W40 is used in the gas engines of LPG, CNG and dual fuel vehicles (gasoline or diesel + CNG or LPG). High quality allows better engine protection and durability, as well as extending oil change intervals to meet specific manufacturer requirements.

PERFORMANCE LEVELS AND APPROVALS

API SN/CF
ACEA C3-16
BMW LL 04

TYPICAL CHARACTERISTICS

Xtreme 8005 C3 ECO GAS 5W40	TESTING PROCEDURE	TYPICAL VALUES
SAE grade		5W-40
Density, kg/m ³	ASTM D 1298	850
Kinematic viscosity, cSt a 40°C	ASTM D 445	85,25
Kinematic viscosity, cSt a 100°C	ASTM D 445	14,0
Viscosity index	ASTM D 2270	170
Pour point, °C	ASTM D 97	≤ -33
Flash point, °C	ASTM D 92	≥ 210
TBN, mg KOH/g	ASTM D 2896	8,0
Sulfated ash, %	ASTM D 874	≤ 0,8

MSDS of all products are available on request