

PRODUCT DESCRIPTION

Xtreme 8002 C2/C3 ECO SYNT 5W-30 is a fully synthetic lubricant formulated with base oils and special additives for modern gasoline and diesel engines, specifically designed to extend the life and maintain the efficiency of particulate filters in all operating conditions.

Xtreme 8002 C2/C3 ECO SYNT 5W-30 provides the following advantages:

- Prolonged life and maintained efficiency of particulate filters for diesel engines and catalysts for gasoline engines,
- Extended service intervals,
- Excellent anti-wear protection over a wide temperature range,
- Better protection against the formation of sludge,
- excellent performance at high and low temperatures,
- Excellent thermal stability and oxidation resistance.

APPLICATIONS

Xtreme 8002 C2/C3 ECO SYNT 5W-30 is recommended in all new generations cars with gasoline and diesel engines with exhaust emission control systems (EGR, SCR, DPF, TWR). Furthermore, it can be used in SUV, light trucks and vans.

PERFORMANCE LEVELS AND APPROVALS

API SN
ACEA C2, C3-16
MB 229.51
VW 505.00/505.01
BMW LL-04
FIAT 9.55535-S1/S3

TYPICAL CHARACTERISTICS

Xtreme 8002 C2/C3 ECO SYNT 5W-30	Testing Procedure	Typical values
SAE Viscosity Grade		5W-30
Density at 15°C, Kg/m ³	ASTM D 1298	850,0
Viscosity at 100°C, cSt	ASTM D 445	10,9
Viscosity Index	ASTM D 2270	168
Pour Point, °C	ASTM D 97	-36
Flash Point, °C	ASTM D 92	215
TBN, mg KOH/g	ASTM D 2896	≥ 6
Sulfated ash, %p	ASTM D 874	≤0,8