

PRODUCT DESCRIPTION

The Xtreme SAE 30, SAE 40 and SAE 50 products are monograde mineral-based oils that have different viscosity grades. They are used in gasoline and diesel vehicles where a monograde product is required.

APPLICATIONS

The Xtreme SAE 30, SAE 40 and SAE 50 products ensure the protection of vehicle engines operating in different climatic and operating conditions.

Characteristics of these lubricants are:

- high protection against wear,
- high protection against varnish, sludge, and other pollutants,
- good protection against acid products deriving from the combustion of diesel fuel with high sulphur content.

PERFORMANCE LEVELS AND APPROVALS

API SF / CD

TYPICAL CHARACTERISTICS

Xtreme SAE 30/40/50	TEST PROCEDURE	TYPICAL VALUES		
		30	40	50
SAE Viscosity Grade		30	40	50
Density @15°C, kg/m ³	ASTM D 1298	≥ 870	≥875	≥880
Kinematic viscosity @100°C, cSt	ASTM D 445	11,0	14,5	17,4
Viscosity Index	ASTM D 2270	≥ 100	≥ 98	≥ 98
Pour Point, °C	ASTM D 97	≤-18	≤-15	≤-15
Flash Point, °C	ASTM D 92	220	226	230