

PRODUCT DESCRIPTION

Xtreme PREMIUM 0W30 C2 is a 100% synthetic lubricant made with carefully selected components, including PAO (polyalphaolefins) and high-tech additives to provide exceptional performance in the latest generation gasoline or diesel engines from PEUGEOT and CITROEN group.

Xtreme PREMIUM 0W30 C2 guarantees the following features:

- High resistance to oxidation which reduces the formation of deposits,
- High thermal stability that allows greater resistance to severe thermal stress,
- Good detergent / dispersant properties that allow cleaner motors and mud protection,
- Excellent anti-wear properties,
- High fluidity at low temperature.

Xtreme PREMIUM 0W30 C2 is formulated with additives with low sulphated ash content and reduced sulfur and phosphorous content (mid-SAPS) that promote protection and extend the life of modern after-treatment systems such as SCR and DPF. In addition to protecting the filters, it ensures:

- High reduction in fuel consumption,
- Maximum power output and engine response speed,
- Reduction of harmful emissions,
- Excellent low temperature properties that guarantee a good cold start of the engine with low oil consumption.

APPLICATIONS

Xtreme PREMIUM 0W30 C2 is recommended for gasoline engines and some diesel engines with DPF that must meet the PSA B712312 specification, it is also compatible with the emission limits EURO 4, EURO 5 and EURO 6.

PERFORMANCE LEVELS AND APPROVALS

ACEA C2-16
PSA B712312

TYPICAL CHARACTERISTICS

Xtreme PREMIUM 0W30 C2	TESTING PROCEDURE	TYPICAL VALUES
SAE grade		0W-30
Density, kg/m ³	ASTM D 1298	840
Kinematic viscosity, cSt a 100°C	ASTM D 445	10,1
Viscosity index	ASTM D 2270	175
Pour point, °C	ASTM D 97	- 39
Flash point, °C	ASTM D 92	220
Sulfated ash, %	ASTM D 874	0,8
TBN , mg KOH/g	ASTM D 2896	7,0

MSDS of all products are available on request