

**PRODUCT DESCRIPTION**

Xtreme UNIVERSAL STAUFFER is composed of selected mineral oils and Calcium soap with additives that offer excellent adhesion to metal surfaces and high resistance to water washout.

Xtreme UNIVERSAL STAUFFER guarantees:

- Great resistance to leaching with water,
- Very good resistance to oxidation,
- Excellent adhesion to metal surfaces,
- Low tendency to separate oil,
- Stability and resistance to shear,
- Good resistance to corrosion and rust
- Very good pumpability in centralized system.

**APPLICATIONS**

Xtreme UNIVERSAL STAUFFER is suitable for the lubrication of frame (chassis) of vehicles and agricultural machinery. This product can also be used in applications which come into contact with water and fertilization gearing operating temperatures up to 80 degrees Celsius and a low or moderate load condition.

Xtreme UNIVERSAL STAUFFER is recommended for use at operating temperatures from -20°C to +80°C.

**PERFORMANCE LEVELS AND APPROVALS**

DIN 51825: K2E-20

**TYPICAL CHARACTERISTICS**

Xtreme UNIVERSAL STAUFFER	TESTING PROCEDURE	TYPICAL VALUES
Thickener		Calcium
Oil component		Mineral
Color		Green
NLGI Grade		2
Worked penetration (60 strokes),dmm	ASTM D-217	265-295
Dropping Point, °C	ASTM D-566	90
Base oil viscosity @ 40°C, cSt	ASTM D-445	90
Copper Corrosion, (adm)	ASTM D-4048	1b
Rust Protection, rating	ASTM D-1743	pass
Oil separation, mass %	ASTM D-1742	< 5