

PRODUCT DESCRIPTION

Xtreme PRO MS is a fluid formulated with vegetable base oil and special additives that guarantees the protection of both the chain saw driven by an internal combustion engine or an electric motor. Thanks to its characteristics this product is suitable for use in winter, it lubricates and protects the chain of chainsaws, increasing the service life and minimizing the risk of breakage of the same.

Xtreme PRO MS shows the following characteristics:

- maximum protection of the chain and the bar,
- good friction and wear protection,
- high rust protection,
- non-toxic and cleanliness.

APPLICATIONS

Xtreme PRO MS is recommended for lubrication bar and chainsaws that works in environmentally sensitive areas. This product should be storage store indoors. If outdoor storage is unavoidable, keep the packaging in a horizontal position, to prevent water infiltration and disappearing of writing on them. Do not keep at temperatures above 60° C, in areas exposed to the sun's heat and frost.

PERFORMANCE LEVELS AND APPROVALS

Xtreme PRO MS meets the requirements of the most important manufacturers of chainsaws and the most stringent environmental regulations.

TYPICAL CHARACTERISTICS

XTREME PRO MS	TESTING PROCEDURE	TYPICAL VALUES
Density @15°C, kg/m ³	ASTM D 1298	≥910,0
Kinematic viscosity @40°C, cSt	ASTM D 445	≥41,5
Viscosity index	ASTM D 2270	≥200
Pour point, °C	ASTM D 97	≤-6
Flash point, °C	ASTM D 92	≥260
Biodegradability, % w	CAC-L-33-T-82	>90