

PRODUCT DESCRIPTION

Xtreme 5W30 D1 is a 100% synthetic lubricant formulated with base oils and high-tech additives to provide exceptional performance for gasoline and diesel engines, offering excellent protection against high temperatures even in extreme operating conditions.

Xtreme 5W30 D1 provides the following advantages:

- Prolonged life and maintained efficiency of particulate filters for diesel engines and catalysts for gasoline engines,
- Extended service intervals,
- High detergent / dispersant properties that allow cleaner motors and mud protection,
- Outstanding protection against sludge, engine rust and corrosion under severe operating conditions,
- Easy starting and rapid oil circulation during cold start,
- Excellent thermal stability and oxidation resistance.

APPLICATIONS

Xtreme 5W30 D1 is recommended for passenger cars with American and Soviet-made gasoline engines, SUVs and light vans that require oil that meets API SN-RC and ILSAC GF-5 specifications. This product is suitable for gasoline engines with fuel injection, turbocharging and multivalve.

PERFORMANCE LEVELS AND APPROVALS

API SN-RC
ILSAC GF-5
CHRYSLER MS 6395
GENERAL MOTORS Dexos1 Gen 2
FIAT 9.55535-CR1

TYPICAL CHARACTERISTICS

Xtreme 5W30 D1	TESTING PROCEDURE	TYPICAL VALUES
SAE grade		5W-30
Density, kg/m ³	ASTM D 1298	≥ 845
Kinematic viscosity, cSt a 100°C	ASTM D 445	9,5 -12,3
Viscosity index	ASTM D 2270	≥ 155
Pour point, °C	ASTM D 97	≤ -33
Flash point, °C	ASTM D 92	≥ 210
TBN, mg KOH/g	ASTM D 2896	≥ 8
Sulfated ash,%	ASTM D 874	≤ 1