

PRODUCT DESCRIPTION

Xtreme 5005 5W40 is a synthetic multi-grade lubricant formulated with high quality base oil and selected additives, among which the friction modifier. The synthetic base oil gives excellent high temperature performance and protection.

Xtreme 5005 5W40 gives the following main benefits:

- excellent low temperature fluidity that gives fast oil flow on startup,
- high oxidation resistance which reduces deposit formation,
- good detergency/dispersion properties for the best control of soot giving cleaner engines,
- enhanced engine protection against wear.

APPLICATIONS

Xtreme 5005 5W40 was developed specifically for vehicles that require an oil that meets the MB 229.5 specification.

Xtreme 5005 5W40 is intended for use in service typical of gasoline and of indirect-injected diesel engines, naturally aspirated or turbocharged, for passenger cars and light vans.

It gives an excellent performance in engines operating under vehicle manufacturer's recommended maintenance procedures.

PERFORMANCE LEVELS

API SN/CF
ACEA A3/B4
MB 229.3/229.5
BMW LL 01
VW 502.00/505.00

TYPICAL CHARACTERISTICS

Xtreme 5005 5W40	TESTING PROCEDURE	TYPICAL VALUES
SAE grade	-	5W40
Density @15°C, kg/m ³	ASTM D 1298	≥850
Kinematic viscosity @100°C, cSt	ASTM D 445	12,5÷16,3
Viscosity index	ASTM D 2270	≥160
Pour point, °C	ASTM D 97	≤-33
Flash point, °C	ASTM D 92	≥220
TBN	ASTM D 2896	≥10