

PRODUCT DESCRIPTION

Xtreme 2T PRO is a semi-synthetic lubricant designed for two-stroke engines of scooters and low-powered motorcycles, suitable for use with any type of gasoline, cooled both with air and liquid for low-speed motorcycles with separate mixer and manual mixing.

Xtreme 2T PRO guarantees:

- Excellent anti-wear protection,
- Extraordinary oxidation resistance and thermal stability,
- High anti-corrosion and anti-rust protection.

Xtreme 2T PRO is formulated with a mixture of mineral and synthetic base oils and a package of additives that offer the following advantages:

- Increased useful life of the engine,
- Reduction of deposits in spark plugs and exhaust lights,
- Reduced exhaust fumes.

APPLICATIONS

Xtreme 2T PRO is suitable for two-stroke engines of low-speed motorcycles, scooters and engines of gardening equipment such as lawnmowers, brush cutters, hedge trimmers, and chainsaws. Suitable for all lubrication systems with direct injection or premixing, in the presence of gasoline with or without lead.

PERFORMANCE LEVELS AND APPROVALS

API TC
JASO FD

TYPICAL CHARACTERISTICS

Xtreme 2T PRO	TESTING PROCEDURE	TYPICAL VALUES
Color	Visual	Red
Density, kg/m ³	ASTM D 1298	≥850
Kinematic viscosity, cSt a 100°C	ASTM D 445	≥8,5
Viscosity index	ASTM D 2270	≥ 150
Pour point, °C	ASTM D 97	≤-21
Flash point, °C	ASTM D 92	≥ 200

MSDS of all products are available on request