

PRODUCT DESCRIPTION

Xtreme MOTO 4T 20W-50 is an oil formulated with carefully selected bases and specific additives which make it particularly suitable for all modern 4-stroke engines.

Xtreme MOTO 4T 20W-50 guarantees the following characteristics:

- Excellent anti-wear and anti-friction capacity,
- Outstanding oxidation resistance and thermal stability,
- High detergency/dispersion capacity with resistance to deposit formation.
- Excellent low and high temperature performance under continuous driving conditions.

Xtreme MOTO 4T 20W-50 is specific to optimize the performance and protection of motorcyclists' engines. It is also suitable for all 4-stroke motorcycle engines, where a lubricant with API SM and JASO MA specifications is required.

APPLICATIONS

Xtreme MOTO 4T 20W-50, with its balanced formula, allows to reduce power losses due to friction and to maintain maximum performance even at high rotation speeds. Furthermore, it ensures the perfect functioning of the clutch discs, avoiding slippage and premature wear of the lubrication systems of the engine and transmission joints.

PERFORMANCE LEVELS AND APPROVALS

.API SM
JASO MA

TYPICAL CHARACTERISTICS

Xtreme Moto 4T 20W-50	TESTING PROCEDURE	TYPICAL VALUES
SAE grade		20W-50
Density, kg/m ³	ASTM D 1298	≥855
Kinematic viscosity, cSt a 100°C	ASTM D 445	16,3 ÷ 21,9
Viscosity index	ASTM D 2270	≥145
Pour point, °C	ASTM D 97	≤-24
Flash point, °C	ASTM D 92	≥ 220

MSDS of all products are available on request