

PRODUCT DESCRIPTION

Xtreme ATF S is formulated with synthetic base oils and an appropriate additive package in order to give the product the properties required by DEXRON III and MERCON automatic transmissions.

This lubricant shows the following properties:

- high Viscosity Index,
- good thermal and oxidation stability,
- good properties at low temperature,
- good Compatibility with metals and elastomers used.

APPLICATIONS

Xtreme ATF S is recommended for automatic gearboxes, power steering systems, torque converters, hydraulic systems and all those automatic transmissions where a product ATF Dexron III or MERCON is required.

The main advantages are:

- high wear protection in case of high speed, torque and impact loads,
- excellent anti-corrosion properties,
- enhanced friction durability prolongs transmission life and promotes smooth shifting,
- increased clutch band and clutch pack capacity.

PERFORMANCE LEVELS AND APPROVALS

GM DEXRON III-E/F/G/H
FORD MERCON/FORD M2C138-CJ/ M2C 166-H
ALLISON C4/ALLISON TES 389
BMW LT 71141/LA 2634/ ETL 7045E/BMW 8072B
CAT-T02
FIAT 9.55550 AG1/AG2/AV1/AV2/AV4
HONDA ATF Z1
KIA SP III
MB 236.1/236.3/236.5/236.6/236.7/236.9/236.10/236.11
MAN 339-Z1/V1/Z2/V2
MAZDA ATF M-III/M5
NISSAN AT MATIC D/J/K Fluid
SUBARU ATF/ATF-HP
VOITH55.6335 (G607)/55.6336
VOLVO 97340/VOLVO Std.1273,4
VW/AUDI G 052-025/G 052-990
TOYOTA TYPE-III/T-IV
ZF TE-ML 02F/03D/04D/09/11A/14A/14B/17C
ZF LIGEGUARD 5

TYPICAL CHARACTERISTICS

Xtreme ATF S	TESTING PROCEDURE	TYPICAL VALUES
Color	Visual	Red
Density@15°C, kg/m ³	ASTM D 1298	≥846,0
Kinematic viscosity @40°C,.cSt	ASTM D 445	≥35,0
Kinematic viscosity @100°C, cSt	ASTM D 445	≥7,2
Viscosity index	ASTM D 2270	≥165
Pour point,°C	ASTM D 97	≤-36
Flash Point,°C	ASTM D 92	≥210