

PRODUCT DESCRIPTION | Xtreme INBOARD 4T 10W-40 is a high-performance synthetic multigrade lubricant designed for use in 4-stroke diesel and gasoline inboard engines.

Xtreme INBOARD 4T 10W-40 features the following characteristics:

- Excellent protection against wear and corrosion in saline environments,
- High oxidation resistance and excellent engine cleanliness,
- Good detergency and dispersancy to reduce deposit formation,
- Outstanding low-temperature properties ensuring quick lubrication during cold starts.

APPLICATIONS | Xtreme INBOARD 4T 10W-40 is ideal for all types of diesel and gasoline engines in the marine sector and for MERCURY, SELVA, SUZUKY, TOHATSU, VOLVO PENTA, and YAMAHA groups. Additionally, it can be used in turbocharged and non-turbocharged diesel and gasoline engines. It is recommended to adhere to the specifications and standards of engine and boat manufacturers.

PERFORMANCE LEVELS AND APPROVALS | API CG-4/CH-4/CI-4/ SL
ACEA E4/E7
ACEA A3/B4
MB 228.5/228.3
VOLVO VDS-2 / VDS-3
RENAULT RXD LEVEL
DEUTZ DQC III - 18
MAN M 3275
MTU TYPE 3

TYPICAL CHARACTERISTICS

Xtreme INBOARD 4T 10W-40	TESTING PROCEDURE	TYPICAL VALUES
SAE grade	-	10W-40
Density @15°C, kg/m ³	ASTM D 1298	≥ 855,0
Kinematic Viscosity @100°C, cSt	ASTM D 445	12,5 ÷ 16,3
Viscosity Index	ASTM D 2270	≥ 145
Pour Point,°C	ASTM D 97	≤ -30
Flash Point,°C	ASTM D 92	≥220