

PRODUCT DESCRIPTION

Xtreme 2001 5W-20 is a latest generation 100% synthetic lubricant made with carefully selected raw materials and additives formulated for use in the latest generation of gasoline and diesel engines and hybrid technology, ensuring total engine protection even in critical conditions.

Xtreme 2001 5W-20 guarantees the following features:

- Excellent anti-wear capacity,
- Extraordinary oxidation resistance and thermal stability,
- Excellent fluidity at low temperature,
- High detergency/dispersion capacity with resistance to the formation of deposits.

APPLICATIONS

Xtreme 2001 5W-20 has a package of medium-low ash additives which, in addition to maintaining excellent engine performance both in short and long distances, ensures:

- Greater engine cleanliness,
- Better engine protection and durability,
- High reduction in fuel consumption,
- Maximum power output and engine response speed,
- Reduction of harmful emissions.

Xtreme 2001 5W-20 is indicated for use in service of gasoline and diesel engines. Furthermore, it is suitable for hybrid cars and light vans where SAE 5W-20 viscosity is required.

PERFORMANCE LEVELS AND APPROVALS

ACEA C5
API SN
FORD WSS M2C948-B

TYPICAL CHARACTERISTICS

Xtreme 2001 5W-20	TESTING PROCEDURE	TYPICAL VALUES
SAE grade		5W-20
Density, kg/m ³	ASTM D 1298	≥850,0
Kinematic viscosity, cSt a 100°C	ASTM D 445	6,9 ÷ 9,3
Viscosity index	ASTM D 2270	≥160
Pour point, °C	ASTM D 97	≤ -33
Flash point, °C	ASTM D 92	≥ 210
Sulfated ash, %	ASTM D 874	≤ 0,8