# ATF 9 ULV

**PRODUCT DESCRIPTION**

XTREME ATF 9 ULV is a fluid formulated with 100% synthetic base oils and a specially balanced additive package for Mercedes-Benz 9-speed automatic transmissions.

XTREME ATF 9 ULV shows the following characteristics:

- good low temperature lubrication,
- excellent thermal and oxidation stability,
- excellent anti-friction, anti-wear and anti-corrosion properties,
- excellent protection against foam formation,
- improves the efficiency and life of the gears

**APPLICATIONS**

XTREME ATF 9 ULV was specially developed for the MERCEDES BENZ 9G-TRONIC (725.0) transmission. This oil is recommended when MB 236.17 specification is required.

**PERFORMANCE LEVELS AND APPROVALS**

MB 236.17
GM DEXRON ULV ATF
AISIN WARNER AW-2
FORD MERCON ULV
NISSAN MATIC P
ZF Lifeguard Fluid 9 - 9HP

**TYPICAL CHARACTERISTICS**

| **Xtreme ATF 9 ULV** | TESTING PROCEDURE | TYPICAL VALUES |
|---|---|---|
| Colour | -- | Amber |
| Density@15°C, kg/m$^3$ | ASTM D 1298 | ≥ 830,0 |
| Kinematic viscosity @40°C, cSt | ASTM D 445 | ≥ 15,0 |
| Kinematic viscosity @100°C, cSt | ASTM D 445 | ≥ 4,0 |
| Viscosity index | ASTM D 2270 | ≥ 155 |
| Brookfield viscosity@ -40°C, cP | ASTM D 97 | ≤ -42 |
| Flash Point,°C | ASTM D 92 | ≥ 200 |

MSDS of all products are available on request

INFORMATION ON THIS TDS HAS TO BE CONSIDERED UPDATED AT THE DATE OF THE DRAFING, HOWEVER VARIATIONS ON THE FORMULATION OR CHANGES ON THE PERFORMANCE OF THE PRODUCT LATER OCCURRED CAN INFLUENCE THE ACCURACY, IN ANY CASE THE ABOVE INFORMATION IS INDICATIVE, AND IT DOESN'T CONSTITUTE PERFORMING LEVEL OF SALE.