

PRODUCT DESCRIPTION

XTREME ATF 8 SPEED is formulated with 100% synthetic base oils and a carefully balanced additive package to give the product the properties required by modern automatic transmissions up to 8 and 9 speeds.

XTREME ATF 8 SPEED offers:

- Exceptional low temperature performance,
- Improved thermal and oxidation stability,
- Excellent friction properties that ensure smooth gear changes at low temperatures and help prevent transmission vibration,
- Exceptional resistance to the formation of sludge and deposits,
- Extended fluid life.

APPLICATIONS

XTREME ATF 8 SPEED is recommended for modern 8- and 9-speed automatic transmissions in North American, European and Asian passenger cars. Also, for modern 6, 8 and 9-speed ZF automatic transmissions in high-performance cars.

Furthermore, it is recommended for 8-speed AISIN TR80 gearboxes mounted on latest generation cars from manufacturers such as Porsche - VW and AUDI.

Not suitable for use in DCT/DSG (dual clutch) or CVT (stepless automatic) transmissions.

PERFORMANCE LEVELS AND APPROVALS

AISIN OC8 TR-80
AUDI/VW G 055 540
BMW 8322
CHRYSLER/DODGE/JEEP 68157995AA/AB
FIAT 9.5550-AV5
JAGUAR 02JDE26444
LAND ROVER LR023288
VW G060 162 (ZF Lifeguard Fluid 8)
ZF No. S671090312
ZF TE ML 11A/B

TYPICAL CHARACTERISTICS

Xtreme ATF 8 SPEED	TESTING PROCEDURE	TYPICAL VALUES
Colour	Visual	Green
Density@15°C, kg/m ³	ASTM D 1298	≥ 835,0
Kinematic viscosity @40°C, cSt	ASTM D 445	≥ 24,0
Kinematic viscosity @100°C, cSt	ASTM D 445	≥ 5,5
Viscosity index	ASTM D 2270	≥ 160
Brookfield viscosity@ -40°C, cP	ASTM D 97	≤ -34
Flash Point,°C	ASTM D 92	≥ 200

MSDS of all products are available on request