

PRODUCT DESCRIPTION

Xtreme Premium 0W-30 is a 100% synthetic lubricant made with carefully selected base oils including PAO (polyalphaolefin) combined with advanced high-performance additives. It has been formulated to provide exceptional performance in modern gasoline and diesel engines, whether normally aspirated or turbocharged, for the latest generation. Thanks to the special friction modifiers, this oil provides maximum power to the engine and enhances its speed of response. It also helps to resist to strong thermal stress typical of high-power engines, ensuring superior cleanliness over extended periods.

Xtreme Premium 0W-30 presents the following characteristics:

- high-performance antiwear, detergent, and dispersant properties,
- excellent low temperature fluidity,
- outstanding oxidation resistance and thermal stability.

APPLICATIONS

Xtreme Premium 0W-30 contains an additive package that guarantees an optimal protection against the wear on mechanical components, even under severe conditions.

Xtreme Premium 0W-30 represents the maximum point of evolution in the field of high performances lubricants. By using this oil, you can obtain:

- greater engine cleanliness,
- better engine protection,
- maximum power distribution and swift engine response,
- reduction of fuel consumption and harmful emissions.

PERFORMANCE LEVELS AND APPROVALS

API SN/SN PLUS
ACEA C2/C3
MB 229.31/229.51
BMW LL 04
VW 502.00/505.01
FIAT 9.55535-GS1/9.55535-DS1
FORD WSS-M2C950-A
PORSCHE
OPEL OV 040 1547 D30/G30 (GM dexos 2)

TYPICAL CHARACTERISTICS

Xtreme PREMIUM 0W-30	TESTING PROCEDURE	TYPICAL VALUES
SAE grade	-	0W-30
Density @15°C, kg/m ³	ASTM D 1298	≥840,0
Kinematic viscosity @100°C, cSt	ASTM D 445	9,3 ÷ 12,5
Viscosity index	ASTM D 2270	≥ 165
Pour point,°C	ASTM D 97	≤ -39
Flash point,°C	ASTM D 92	≥ 210
TBN, mgKOH/g	ASTM D-2896	≥ 6
Sufated Ash %w/w	ASTM D 874	≤ 0,8