

PRODUCT DESCRIPTION

The Xtreme HYDRO HVI line of products includes 5 hydraulic oils with ISO grades going from ISO 32 to ISO 150 and is formulated with carefully selected bases and balanced additive package to ensure excellent performance in all hydraulic systems operating in a wide temperature range. It has great antifoam properties and antioxidants that ensure longer stays in service.

Its anti-wear characteristics guarantee high levels of protection for all types of pumps. Other gradations are available on request.

The main characteristics are:

- Good fluidity at low temperatures allowing cold start without oil preheating,
- High Viscosity index,
- Excellent demulsibility,
- Great resistance to oxidation and thermal stability,
- Excellent compatibility with metals and seals usually used in hydraulic controls.

APPLICATIONS

Xtreme HYDRO HVI line of products is recommended in hydraulic transmission systems where the fluids are subjected to strong variations of temperatures, and in hydraulic systems where small changes in viscosity with temperature fluctuations are tolerated.

Xtreme HYDRO HVI line of products can be used in all mechanisms and gears unless marked EP features, and in tested machine tools and very loaded bearings.

PERFORMANCE LEVELS AND APPROVALS

ISO 11158 HV	CINCINNATI MILACRON P-68 (ISO 32)
DIN 51524 Part III-HVLP	CINCINNATI MILACRON P-69 (ISO 68)
DENISON HF-0/ HF-1/ HF-2	CINCINNATI MILACRON P-70 (ISO 46)
AFNOR NFE 48-603/48690/48-691	VICKERS I-286-S/M-2950-S

TYPICAL CHARACTERISTICS

Xtreme HYDRO HVI	TESTING PROCEDURE	VAQLORI TIPICI				
		32	46	68	100	150
ISO Viscosity Grade						
Density at 15°C, Kg/m ³	ASTM D 1298	≥849	≥852	≥854	≥864	≥875
Viscosity at 40°C, cSt	ASTM D 445	29,8÷35,2	41,4÷50,6	61,2÷74,8	90,0÷110,0	135÷165
Viscosity at 100°C, cSt	ASTM D 445	6,16	7,98	10,61	14,0	17,1
Viscosity Index	ASTM D 2270	≥143	≥146	≥144	≥143	≥123
Pour Point, °C	ASTM D 97	≤-30	≤-27	≤-24	≤-24	≤-18
Flash Point, °C	ASTM D 92	≥218	≥220	≥225	≥236	≥236