4001 5W-50

PRODUCT DESCRIPTION

Xtreme 4001 5W-50 is a premium quality lubricant blended with synthetic base oils fortified with a balanced component system that provide outstanding performance in many driving situations.

Xtreme 4001 5W-50 shows the following main benefits:

- Excellent low temperature fluidity that gives fast oil flow on start up,
- High oxidation resistance which reduces deposit formation and improve oil life,
- Good detergency/dispersion properties giving cleaner engines,
- Enhanced engine protection against wear,
- Maximizes power output by reducing internal friction by the presence of friction modifier.

APPLICATIONS

Xtreme 4001 5W-50 is suitable for many types of vehicles and operating conditions, from mild to severe. It is intended for use in service typical of gasoline and indirect-injected diesel engines, naturally aspirated or turbocharged, for passenger cars and light vans.

PERFORMANCE LEVELS AND APPROVALS

API SM/CF
ACEA A3/B4
BMW LL-01
MB 229.1/229.3
PORSCHE A40
VW 505.00

TYPICAL CHARACTERISTICS

Xtreme 4001 5W - 50	TESTING PROCEDURE	TYPICAL VALUES
SAE Viscosity Grade		5W-50
Density @15°C, Kg/m^3	ASTM D 1298	≥850
Kinematic viscosity @100°C, cSt	ASTM D 445	16.3÷21,9
Viscosity Index	ASTM D 2270	≥ 155
Pour Point, °C	ASTM D 97	≤-33
Flash Point, °C	ASTM D 92	≥210

INFORMATION ON THIS TDS HAS TO BE CONSIDERED UPDATED AT THE DATE OF THE DRAFING, HOWEVER VARIATIONS ON THE FORMULATION OR CHANGES ON THE PERFORMANCE OF THE PROCUCT LATER OCCURRED CAN INFLUENCE THE ACCURACY, IN ANY CASE THE ABOVE INFORMATION IS INDICATIVE, AND IT DOESN'T CONSTITUTE PERFORMING LEVEL OF SALE.