6001 10W-60

PRODUCT DESCRIPTION

Xtreme 6001 10W-60 is a premium quality lubricant blended with synthetic base oils and selected additives, developed to provide protection under severe driving style and racing conditions.

Xtreme 6001 10W-60 gives longer engine life and shows the following main benefits:

- excellent low temperature fluidity that gives fast oil flow on start up,
- excellent thermal and oxidation stability,
- enhanced engine protection against wear,
- high compatibility with a wide range of seals materials,
- maximizes power output reducing internal friction by the presence of friction modifier.

APPLICATIONS

Xtreme 6001 10W-60 is recommended for gasoline and indirect-injected diesel engines, naturally aspirated or turbocharged, for passenger cars and light vans. Furthermore, is suggested to use in almost all operating conditions of medium to extreme.

PERFORMANCE LEVELS AND APPROVALS

API SM/CF
ACEA A3/B4
BMW LL-01
MB 229.1/229.3
VW 505.00

TYPICAL CHARACTERISTICS

Xtreme 6001 10W-60	TESTING PROCEDURE	TYPICAL VALUES
SAE Viscosity Grade		10W-60
Density @15°C, Kg/m3	ASTM D 1298	≥860
Kinematic viscosity @100°C, cSt	ASTM D 445	21,9÷26,1
Viscosity Index	ASTM D 2270	≥ 155
Pour Point, °C	ASTM D 97	≤-30
Flash Point, °C	ASTM D 92	≥220

MSDS of all products are available on request

INFORMATION ON THIS TDS HAS TO BE CONSIDERED UPDATED AT THE DATE OF THE DRAFING, HOWEVER VARIATIONS ON THE FORMULATION OR CHANGES ON THE PERFORMANCE OF THE PROCUCT LATER OCCURRED CAN INFLUENCE THE ACCURACY, IN ANY CASE THE ABOVE INFORMATION IS INDICATIVE, AND IT DOESN'T CONSTITUTE PERFORMING LEVEL OF SALE.