3007 10W-40

PRODUCT DESCRIPTION

Xtreme 3007 10W-40 is a premium quality multigrade synthetic lubricant blended with isomerised base oil through a severe hydrogenation process and selected additives, designed to achieve the highest performance standards in gasoline and diesel engines.

Xtreme 3007 10W-40 offers the following main advantages:

- good low temperature properties to allow rapid lubrication after cold starting,
- outstanding protection against wear to maximise engine life,
- excellent detergent/dispersant properties for best soot control,
- excellent thermal and oxidation stability increasing fuel economy and extended service intervals.

APPLICATIONS

Xtreme 3007 10W-40 is intended for use in typical gasoline and diesel engine services, including turbo-charged engines in passenger cars, SUVs, light vans and light trucks.
It is suitable for extended drain intervals as specified by engine manufacturers.

PERFORMANCE LEVELS AND APPROVALS

API SN
MB 229.51
VW 505.00/505.01

TYPICAL CHARACTERISTICS

Xtreme 3007 10W-40	TESTING PROCEDURE	RESULTS
SAE grade	-	10W-40
Density @15°C kg/ m3	ASTM D 1298	≥860
Kinematic viscosity @100°C,cSt	ASTM D 445	12,5 ÷ 16,3
Viscosity index	ASTM D 2270	≥130
Pour point, °C	ASTM D 97	≤-30
Flash point, °C	ASTM D 92	≥220

INFORMATION ON THIS TDS HAS TO BE CONSIDERED UPDATED AT THE DATE OF THE DRAFING, HOWEVER VARIATIONS ON THE FORMULATION OR CHANGES ON THE PERFORMANCE OF THE PROCUCT LATER OCCURRED CAN INFLUENCE THE ACCURACY, IN ANY CASE THE ABOVE INFORMATION IS INDICATIVE, AND IT DOESN'T CONSTITUTE PERFORMING LEVEL OF SALE.